

232	renumber as	394
233	"	433
234	"	475
235	"	395
236	"	434
237	"	476
238	"	396
239	"	435
240	"	477
241	"	397
242	"	436
243	"	478
244	"	398
245	"	437
246	"	479
247	"	399
248	"	438
249	"	480
250	"	400
251	"	439
252	"	481
253	"	401
254	"	440
255	"	482
256	"	402
257	"	441
258	"	483
259	"	403
260	"	442
261	"	484
262	"	404
263	"	443
264	"	485
265	"	405
266	"	444
267	"	486
268	"	406
269	"	445
270	"	487
271	"	407
272	"	446
273	"	488
274	"	408
275	"	447
276	"	489
277	"	409

278	renumber as	410
279	"	448
280	"	449
281	"	490
282	"	491
283	"	411
284	"	412
285	"	450
286	"	451
287	"	492
288	"	493
289	"	413
290	"	452
291	"	494
292	"	414
293	"	453
294	"	495
295	"	415
296	"	454
297	"	496
298	"	416
299	"	455
300	"	497
301	"	417
302	"	456
303	"	498
304	"	418
305	"	457
306	"	499
307	"	419
308	"	458
309	"	500
310	"	420
311	"	459
312	"	501
319	"	421
320	"	460
321	"	422
322	"	461
323	"	423
324	"	462
325	"	424
326	"	463
327	"	425
328	"	464
329	"	502
330	"	426

331	renumber as	465
332	"	503
333	"	466
335	"	504
336	"	467
337	"	427
338	"	505
339	"	428
340	"	468
341	"	506
342	"	429
343	"	469
344	"	507
345	"	430
346	"	470
347	"	508
348	"	509
349	"	510
350	"	511
351	"	512
352	"	513
353	"	514
354	"	515
355	"	516
356	"	517
357	"	518
358	"	519
359	"	520
360	"	521
361	"	522
362	"	523
363	"	524
364	"	525
365	"	526
366	"	527
367	"	528
368	"	529
369	"	530
370	"	531
371	"	532
372	"	533
373	"	534
374	"	535
375	"	536
376	"	537
377	"	538

378	renumber as	539
379	"	540
380	"	541
381	"	542
382	"	543
383	"	544
384	"	545
385	"	546
386	"	547
387	"	548
388	"	549
389	"	550.

In the renumbered claims, change all numerical references to other claims to correspond to the new numbers.

It is believed that no fees or charges are due in this response, since is submitted within the one month allowed period. However, if any charges are due, please debit my PTO account number 501 334. If there are any questions, please contact the undersigned at 310 208 6606.



Mitja Hinderks,

Sole inventor, applicant and power-of-attorney of record.

May 29 2003

In my application number 08 /477 704 titled "**Reciprocating Elements and Associated Fluid Flows**" filed on June 7 1995 under group art 3747, WHAT I Mitja Victor Hinderks CLAIM IS:

390. *A rotatable shaft, a mechanism and device for the working of fluids, said device comprising a housing with a cylinder assembly mounted therein, at least one component assembly mounted to reciprocate within said cylinder assembly, said cylinder assembly having at least one first working surface and said component assembly having at least one second working surface such that said working surfaces in operation are approximately parallel and co-axial and variably spaced, said surfaces partly defining at least one fluid working chamber varying in capacity during an operating cycle of said device, means deployed between said cylinder assembly and said component assembly to cause said component assembly and said second surface to rotate while reciprocating relative to said cylinder assembly and said first surface, said component assembly being linked to said shaft by said mechanism, said mechanism causing said shaft to only rotate while said component assembly reciprocates and rotates.*
391. *The device of claim 390, said cylinder assembly being rotatably mounted in said housing.*
392. *A reciprocating combustion engine, including a fuel delivery system, an exhaust emission control system and the device of claim 390.*
393. *The engine of claim 392, said cylinder assembly being rotatably mounted in said housing.*
394. *A compound engine comprising the engine of claim 392, at least one other engine, and a special means for transferring work between each of said at least two engines.*
395. *The compound engine of claim 394, wherein said special means include the flow of heated gases.*
396. *The device of claim 390, wherein said component assembly defines a passage for fluids worked by said device.*
397. *The device of claim 390, including structure which defines a volume at least partially surrounding said cylinder assembly, in operation said volume functioning as a passage for fluids worked by said device.*
398. *The engine of claim 392, wherein said component assembly defines a passage for fluids worked by*

said device.

399. *The engine of claim 392, including structure which defines a volume at least partially surrounding said cylinder assembly, in operation said volume functioning as a passage for fluids worked by said device.*
400. *The engine of claim 398, including filamentary material within said passage.*
401. *The engine of claim 399, including filamentary material within said volume.*
402. *The engine of claim 400, wherein said filamentary material is catalytic to expedite reactions between portions of the working fluids.*
403. *The engine of claim 401, wherein said filamentary material is catalytic to expedite reactions between portions of the working fluids.*
404. *The device of claim 390, including insulating material at least partially encasing said device.*
405. *The engine of claim 392, including insulating material at least partially encasing said engine.*
406. *The device of claim 390, wherein said cylinder assembly is formed at least in part of ceramic material.*
407. *The device of claim 390, wherein said component assembly is formed at least in part of ceramic material.*
408. *The device of claim 390, wherein said component assembly has a first distinct surface and said cylinder assembly a second distinct surface, in operation said distinct surfaces being approximately constantly spaced from and approximately parallel to one another, at least one of said distinct surfaces defining at least one depression wholly fillable by fluids worked by said device.*
409. *The device of claim 390, wherein said cylinder assembly is comprised of portions including at least one element, each said element holding said portions together and being pre-loaded under tension.*
410. *The device of claim 409, wherein said element is of tubular form.*

411. *The device of claim 390, wherein said component assembly is comprised of portions including at least one element, each said element holding said portions together and being pre-loaded under tension.*
412. *The device of claim 411, wherein said element is of tubular form.*
413. *The engine of claim 392, wherein said cylinder assembly is formed at least in part of ceramic material.*
414. *The engine of claim 392, wherein said component assembly is formed at least in part of ceramic material.*
415. *The engine of claim 413, including at least one electrical circuit within said ceramic material.*
416. *The engine of claim 414, including at least one electrical circuit within said ceramic material.*
417. *The rotatable shaft, mechanism and device of claim 390, in which said mechanism comprises a series of splines slidably mounted on another series of splines.*
418. *The rotatable shaft, mechanism and device of claim 390 including rollers, in which said mechanism comprises a series of flanges slidably mounted on another series of flanges, said two series of flanges being separated by said rollers.*
419. *The rotatable shaft, mechanism and device of claim 390, wherein said mechanism comprises at least one bellows.*
420. *The rotatable shaft, mechanism and device of claim 390, wherein said mechanism comprises at least one hinged element.*
421. *The device of claim 390, wherein said means comprise a guide restrained by a single endless substantially sinusoidal path.*
422. *The device of claim 421, wherein said guide is a roller of truncated conical configuration.*
423. *The engine of claim 392, wherein said means comprise a guide restrained by a single endless substantially sinusoidal path.*

424. *The engine of claim 423, wherein said guide is a roller of truncated conical configuration.*
425. *The device of claim 390, wherein said fluid working chamber is at least partially of toroidal configuration.*
426. *The engine of claim 392, wherein said fluid working chamber is at least partially of toroidal configuration.*
427. *The engine of claim 393, wherein said housing comprises insulating material.*
428. *The device of claim 390, wherein said component assembly consists of one monolithic piece.*
429. *The device of claim 390, wherein said component assembly has a projecting portion which at least partly penetrates said segment during at least part of said cycle.*
430. *The engine of claim 392, wherein said component assembly has a projecting portion which at least partly penetrates said segment during at least part of said cycle.*
431. *A rotatable shaft, a mechanism and device for the working of fluids, said device comprising a housing with a cylinder assembly mounted therein, at least one component assembly mounted to reciprocate within said cylinder assembly, said cylinder assembly having at least one first working surface and said component assembly having at least one second working surface such that said working surfaces in operation are approximately parallel and co-axial and variably spaced, said surfaces partly defining at least one fluid working chamber varying in capacity during an operating cycle of said device, means deployed between said cylinder assembly and said component assembly to cause said component assembly and said second surface to rotate while reciprocating relative to said cylinder assembly and said first surface, said component assembly being linked to said shaft by said mechanism, said mechanism causing said shaft to only rotate while said component assembly reciprocates and rotates, said cylinder assembly being rotatably mounted in said housing.*
432. *A reciprocating internal combustion engine, including a fuel delivery system, an exhaust emissions control system and the device of claim 431.*
433. *A compound engine comprising the engine of claim 432, at least one other engine, and a special means for transferring work between each of said at least two engines.*

434. *The compound engine of claim 433, wherein said special means include the flow of heated gases.*
435. *The device of claim 431, wherein said component assembly defines a passage for fluids worked by said device.*
436. *The device of claim 431, including structure which defines a volume at least partially surrounding said cylinder assembly, in operation said volume functioning as a passage for fluids worked by said device.*
437. *The engine of claim 432, wherein said component assembly defines a passage for fluids worked by said device.*
438. *The engine of claim 432, including structure which defines a volume at least partially surrounding said cylinder assembly, in operation said volume functioning as a passage for fluids worked by said device.*
439. *The engine of claim 437, including filamentary material within said passage.*
440. *The engine of claim 438, including filamentary material within said volume.*
441. *The engine of claim 439, wherein said filamentary material is catalytic to expedite reactions between portions of the working fluids.*
442. *The engine of claim 440, wherein said filamentary material is catalytic to expedite reactions between portions of the working fluids.*
443. *The device of claim 431, including insulating material at least partially encasing said device.*
444. *The engine of claim 432, including insulating material at least partially encasing said engine.*
445. *The device of claim 431, wherein said cylinder assembly is formed at least in part of ceramic material.*
446. *The device of claim 431, wherein said component assembly is formed at least in part of ceramic material.*

447. *The device of claim 431, wherein said component assembly has a first distinct surface and said cylinder assembly a second distinct surfaces, in operation said distinct surfaces being approximately constantly spaced from and approximately parallel to one another, at least one of said distinct surfaces defining at least one depression wholly fillable by fluids worked by said device.*
448. *The device of claim 431, wherein said cylinder assembly is comprised of portions including at least one element, each said element holding said portions together and being pre-loaded under tension.*
449. *The device of claim 448, wherein said element is of tubular form.*
450. *The device of claim 431, wherein said component assembly is comprised of portions including at least one element, each said element holding said portions together and being pre-loaded under tension.*
451. *The device of claim 450, wherein said element is of tubular form.*
452. *The engine of claim 432, wherein said cylinder assembly is formed at least in part of ceramic material.*
453. *The engine of claim 432, wherein said component assembly is formed at least in part of ceramic material.*
454. *The engine of claim 452, including at least one electrical circuit within said ceramic material.*
455. *The engine of claim 453, including at least one electrical circuit within said ceramic material.*
456. *The rotatable shaft, mechanism and device of claim 431, in which said mechanism comprises a series of splines slidably mounted on another series of splines.*
457. *The rotatable shaft, mechanism and device of claim 431 including rollers, in which said mechanism comprises a series of flanges slidably mounted on another series of flanges, said two series of flanges being separated by said rollers.*
458. *The rotatable shaft, mechanism and device of claim 431, wherein said mechanism comprises at least one bellows.*

459. *The rotatable shaft, mechanism and device of claim 431, wherein said mechanism comprises at least one hinged element.*
460. *The device of claim 431, wherein said means comprise a guide restrained by a single endless substantially sinusoidal path.*
461. *The device of claim 460, wherein said guide is a roller of truncated conical configuration.*
462. *The engine of claim 432, wherein said means comprise a guide restrained by a single endless substantially sinusoidal path.*
463. *The engine of claim 462, wherein said guide is a roller of truncated conical configuration.*
464. *The device of claim 431, wherein said fluid working chamber is at least partially of toroidal configuration.*
465. *The engine of claim 432, wherein said fluid working chamber is at least partially of toroidal configuration.*
466. *The device of claim 431, wherein said housing comprises insulating material.*
467. *The engine of claim 432, wherein said housing comprises insulating material.*
468. *The device of claim 431, wherein said component assembly consists of one monolithic piece.*
469. *The device of claim 431, wherein said component assembly has a projecting portion which at least partly penetrates said segment during at least part of said cycle.*
470. *The engine of claim 432, wherein said component assembly has a projecting portion which at least partly penetrates said segment during at least part of said cycle.*
471. *A rotatable shaft, a mechanism and device for the working of fluids, said device comprising a housing with a cylinder assembly mounted therein, at least one component assembly mounted to reciprocate within said cylinder assembly, said cylinder assembly having at least one working surface and said component assembly having at least one second working surface such that said working surfaces in operation are approximately parallel and co-axial and variably spaced, said*

surfaces partly defining at least one fluid working chamber varying in capacity during an operating cycle of said device, each of said surfaces being of endless wave-like configuration to permit and limit said component assembly and said second surface to both reciprocate and rotate relative to said cylinder assembly and said first surface, said mechanism causing said shaft to only rotate while said component assembly reciprocates and rotates.

472. *The device of claim 471, said cylinder assembly being rotatably mounted in said housing.*
473. *A reciprocating internal combustion engine, including a fuel delivery system, an exhaust emissions control system and the device of claim 471.*
474. *The engine of claim 473, said cylinder assembly being rotatably mounted in said housing.*
475. *A compound engine comprising the engine of claim 473, at least one other engine, and a special means for transferring work between each of said at least two engines.*
476. *The compound engine of claim 475, wherein said special means include the flow of heated gases.*
477. *The device of claim 471, wherein said component assembly defines a passage for fluids worked by said device.*
478. *The device of claim 471, including structure which defines a volume at least partially surrounding said cylinder assembly, in operation said volume functioning as a passage for fluids worked by said device.*
479. *The engine of claim 473, wherein said component assembly defines a passage for fluids worked by said device.*
480. *The engine of claim 473, including structure which defines a volume at least partially surrounding said cylinder assembly, in operation said volume functioning as a passage for fluids worked by said device.*
481. *The engine of claim 480, including filamentary material within said passage.*
482. *The engine of claim 480, including filamentary material within said volume.*

483. *The engine of claim 481, wherein said filamentary material is catalytic to expedite reactions between portions of the working fluids.*
484. *The engine of claim 482, wherein said filamentary material is catalytic to expedite reactions between portions of the working fluids.*
485. *The device of claim 471, including insulating material at least partially encasing said device.*
486. *The engine of claim 473, wherein said cylinder assembly is formed at least in part of ceramic material.*
487. *The device of claim 471, wherein said cylinder assembly is formed at least in part of ceramic material.*
488. *The device of claim 471, wherein said component assembly is formed at least in part of ceramic material.*
489. *The device of claim 471, wherein said component assembly has a first distinct surface and said cylinder assembly a second distinct surfaces, in operation said distinct surfaces being approximately constantly spaced from and approximately parallel to one another, at least one of said distinct surfaces defining at least one depression wholly fillable by fluids worked by said device.*
490. *The device of claim 471, wherein said cylinder assembly is comprised of portions including at least one element, each said element holding said portions together and being pre-loaded under tension.*
491. *The device of claim 490, wherein said element is of tubular form.*
492. *The device of claim 471, wherein said component assembly is comprised of portions including at least one element, each said element holding said portions together and being pre-loaded under tension.*
493. *The device of claim 492, wherein said element is of tubular form.*
494. *The engine of claim 473, wherein said cylinder assembly is formed at least in part of ceramic material.*

495. *The engine of claim 473, wherein said component assembly is formed at least in part of ceramic material.*
496. *The engine of claim 494, including at least one electrical circuit within said ceramic material.*
497. *The engine of claim 495, including at least one electrical circuit within said ceramic material.*
498. *The rotatable shaft, mechanism and device of claim 471, in which said mechanism comprises a series of splines slidably mounted on another series of splines.*
499. *The rotatable shaft, mechanism and device of claim 471 including rollers, in which said mechanism comprises a series of flanges slidably mounted on another series of flanges, said two series of flanges being separated by said rollers.*
500. *The rotatable shaft, mechanism and device of claim 471, wherein said mechanism comprises at least one bellows.*
501. *The rotatable shaft, mechanism and device of claim 371, wherein said mechanism comprises at least one hinged element.*
502. *The device of claim 471, wherein said fluid working chamber is at least partially of toroidal configuration.*
503. *The engine of claim 473, wherein said fluid working chamber is at least partially of toroidal configuration.*
504. *The device of claim 472, wherein said housing comprises insulating material.*
505. *The engine of claim 474, wherein said housing comprises insulating material.*
506. *The device of claim 471, wherein said component assembly consists of one monolithic piece.*
507. *The device of claim 471, wherein said component assembly has a projecting portion which at least partly penetrates said segment during at least part of said cycle.*
508. *The engine of claim 473, wherein said component assembly has a projecting portion which at least*

partly penetrates said segment during at least part of said cycle.

509. *A rotatable shaft, a mechanism and device for the working of fluids, said device comprising a housing with a cylinder assembly mounted therein, at least one component mounted to reciprocate within said cylinder assembly, said cylinder assembly having at least one working surface and said component having at least one second working surface such that said working surfaces in operation are approximately parallel and co-axial and variably spaced, said surfaces partly defining at least one fluid working chamber varying in capacity during an operating cycle of said device, means deployed between said cylinder assembly and said component to cause said component and said second surface to rotate while reciprocating relative to said cylinder assembly and said first surface, said mechanism causing said shaft to only rotate while said component assembly reciprocates and rotates, said housing including substantial insulating material.*
510. *The device of claim 509, said cylinder assembly being rotatably mounted in said housing.*
511. *A reciprocating internal combustion engine, including a fuel delivery system, an exhaust emissions control system and the device of claim 509.*
512. *The engine of claim 511, said cylinder assembly being rotatably mounted in said housing.*
513. *A compound engine comprising the engine of claim 511, at least one other engine, and a special means for transferring work between each of said at least two engines.*
514. *The compound engine of claim 513, wherein said special means include the flow of heated gases.*
515. *The device of claim 509, wherein said component assembly defines a passage for fluids worked by said device.*
516. *The device of claim 509, including structure which defines a volume at least partially surrounding said cylinder assembly, in operation said volume functioning as a passage for fluids worked by said device.*
517. *The engine of claim 511, wherein said component assembly defines a passage for fluids worked by said device.*
518. *The engine of claim 511, including structure which defines a volume at least partially surrounding*

page 12

said cylinder assembly, in operation said volume functioning as a passage for fluids worked by said device.

519. *The engine of claim 517, including filamentary material within said passage.*
520. *The engine of claim 518, including filamentary material within said volume.*
521. *The engine of claim 519, wherein said filamentary material is catalytic to expedite reactions between elements of the working fluids.*
522. *The engine of claim 520, wherein said filamentary material is catalytic to expedite reactions between elements of the working fluids.*
523. *The device of claim 509, including insulating material at least partially encasing said device.*
524. *The engine of claim 511, wherein said cylinder assembly is formed at least in part of ceramic material.*
525. *The device of claim 509, wherein said cylinder assembly is formed at least in part of ceramic material.*
526. *The device of claim 509, wherein said component assembly is formed at least in part of ceramic material.*
527. *The device of claim 509, wherein said component assembly has a first distinct surface and said cylinder assembly a second distinct surfaces, in operation said distinct surfaces being approximately constantly spaced from and approximately parallel to one another, at least one of said distinct surfaces defining at least one depression wholly fillable by fluids worked by said device.*
528. *The device of claim 509, wherein said cylinder assembly is comprised of portions including at least one element, each said element holding said portions together and being pre-loaded under tension.*
529. *The device of claim 528, wherein said element is of tubular form.*
530. *The device of claim 509, wherein said component assembly is comprised of portions including at*

least one element, each said element holding said portions together and being pre-loaded under tension.

531. *The device of claim 530, wherein said element is of tubular form.*
532. *The engine of claim 511, wherein said cylinder assembly is formed at least in part of ceramic material.*
533. *The engine of claim 511, wherein said component assembly is formed at least in part of ceramic material.*
534. *The engine of claim 532, including at least one electrical circuit within said ceramic material.*
535. *The engine of claim 533, including at least one electrical circuit within said ceramic material.*
536. *The rotatable shaft, mechanism and device of claim 509, in which said mechanism comprises a series of splines slidably mounted on another series of splines.*
537. *The rotatable shaft, mechanism and device of claim 509 including rollers, in which said mechanism comprises a series of flanges slidably mounted on another series of flanges, said two series of flanges being separated by said rollers.*
538. *The rotatable shaft, mechanism and device of claim 509, wherein said mechanism comprises at least one bellows.*
539. *The rotatable shaft, mechanism and device of claim 509, wherein said mechanism comprises at least one hinged element.*
540. *The device of claim 509, wherein said means comprise a guide restrained by a single endless substantially sinusoidal path.*
541. *The device of claim 540, wherein said guide is a roller of truncated conical configuration.*
542. *The engine of claim 511, wherein said means comprise a guide restrained by a single endless substantially sinusoidal path.*

page 14

543. *The engine of claim 542, wherein said guide is a roller of truncated conical configuration.*
544. *The device of claim 509, wherein said fluid working chamber is at least partially of toroidal configuration.*
545. *The engine of claim 511, wherein said fluid working chamber is at least partially of toroidal configuration.*
546. *The device of claim 510, wherein said housing comprises insulating material.*
547. *The engine of claim 512, wherein said housing comprises insulating material.*
548. *The device of claim 509, wherein said component assembly consists of one monolithic piece.*
549. *The device of claim 509, wherein said component assembly has a projecting portion which at least partly penetrates said segment during at least part of said cycle.*
550. *The engine of claim 511, wherein said component assembly has a projecting portion which at least partly penetrates said segment during at least part of said cycle.*
-

END OF CLAIMS